

(EN) **DECLARATION OF PERFORMANCE**

according to Regulation (EU) 305/2011

No. H07900146-CPR-2014/04/23

- |    |  |   |
|----|--|---|
| 1. | Unique identification code of the product type :   | <b>SL30-01</b> , Room heater burning solid fuel without hot water supply<br><b>EN13240:2001/A2:2004/AC:2007</b>   |
| 2. | Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):                   | <b>BRUNICO BCS, CANAZEI BCS, E925 BCS, E926 BCS, E927 D BCS, E927 M BCS</b>   |
| 3. | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | <b>Room heater burning solid fuel without hot water supply</b>  |
| 4. | Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):                         | <b>PIAZZETTA</b><br>Gruppo Piazzetta S.p.A.<br>Via Montello, 22 - 31011 Casella d'Asolo (TV) – Italy<br>Tel. +3904235271 Fax: +39042355178 email: info@gruppopiazzetta.com          |
| 5. | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):                   | -   |
| 6. | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:                          | <b>System 3 and System 4</b>  |
| 7. | In case of the declaration of performance concerning a construction product covered by a harmonised standard:  | <b>The notified laboratory IMQ PRIMACONTROL No 1881 performed the determination of the product type on the basis of type testing under system 3 and issued test report CPR14015</b> |

8. Declared performance

Essential Characteristics	Performance	Harmonized technical specification
<b>Fire safety</b>		
Reaction to fire	A1	EN13240:2001/A2:2004/AC:2007
Distance to combustible materials	Minimum distances, in cm rear = 25 sides = 30 ceiling = - front = 100 floor = -	EN13240:2001/A2:2004/AC:2007
Risk of burning fuel falling out	Pass	EN13240:2001/A2:2004/AC:2007
<b>Emission of combustion products</b>		
at nominal heat output	CO [ 0,090 % ] NOx [ 79,00 mg/Nm <sup>3</sup> ] THC [ 18,00 mg/Nm <sup>3</sup> ] PM [ 10,0 mg/Nm <sup>3</sup> ]	EN13240:2001/A2:2004/AC:2007
<b>Surface Temperature</b>	Pass	EN13240:2001/A2:2004/AC:2007
<b>Electrical safety</b>	Pass	EN 60335-2-102: 2007/A1:2011
<b>Cleanability</b>	Pass	EN13240:2001/A2:2004/AC:2007
<b>Maximum operating pressure</b>	- bar	EN13240:2001/A2:2004/AC:2007
<b>Flue gas temperature at nominal heat output</b>	T [292,0 °C ]	EN13240:2001/A2:2004/AC:2007
<b>Mechanical resistance (to carry a chimney/flue)</b>	NPD ( no performance determined )	EN13240:2001/A2:2004/AC:2007
<b>Thermal output</b>		
Nominal heat output	6,0 kW	EN13240:2001/A2:2004/AC:2007
Room heating output	6,0 kW	
<b>Energy efficiency</b>		
at nominal heat output	η [81,4 % ]	EN13240:2001/A2:2004/AC:2007

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by Carlo Piazzetta ( Chief Executive Officer )

Casella d'Asolo , 2014/04/23



(signature )