



## DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

## N. 79

Unique identification code of the product-type : M 80

2. Type, batch or serial number (Art. 11-4) : M 60 - M 70 - M 80

Intended use or uses of the construction Cooker burning and domestic 3. product, in accordance with the applicable heating solid fuel harmonised technical specification

Name or registered trademark of the Rizzoli S.r.l. manufacturer (Art. 11-5)

5. Name and address of the manufacturer

System of assessment and verification of 6. : System 3 constancy of performance (Attachment 5)

ACTECO s.r.l. - (N.B. 1880) : I-33084 Cordenons (PN) 7. Notified laboratory

Via Amman, 41 Issued test report : 1880-CPR-041-15

8. Declared performance

Harmonized technical specification : EN 12815:2001/A1:2004/AC:2007

**Essential characteristics Performance** 

Reaction to fire

Minimum distances, in mm: Distance to combustible materials : rear = 250, sides = 70, floor = 0,

ceiling = 600, front = 800

Risk of burning fuel falling out : Pass

Emission of combustion products CO [0,07 %]

Surface temperature : Pass Electrical safety : Pass Cleanability : Pass Maximum water operating pressure -- bar Flue gas temperature at nominal heat output

: T [191,4 °C]

Mechanical resistance NPD Nominal heat output 8,0 kW 8,0 kW Room heating output Water heating output -- kW **Energy efficiency** : n [80,2 %]

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Trodena n.P.N., November 16<sup>th</sup> 2015

