

DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

N. 113

1.	Unique identification code of the product-type	:	M 80 M 60 - M 70 - M 80
2.	Type, batch or serial number (Art. 11-4)	:	M 80 - M 70 - M 80 MZ 60 - MZ 70 - MZ 80 ML 60 - ML 80
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification	:	Cooker burning and domestic heating solid fuel
4.	Name or registered trademark of the manufacturer (Art. 11-5)	:	Rizzoli S.r.l.
5.	Name and address of the manufacturer	:	
6.	System of assessment and verification of constancy of performance (Attachment 5)	:	System 3
7.	Notified laboratory	:	ACTECO s.r.l (N.B. 1880) I-33084 Cordenons (PN) Via Amman, 41
	Issued test report	:	1880-CPR-041-15 1880-CPR-056-17
8.	Declared performance		
	Harmonized technical specification	:	EN 12815:2001/A1:2004/AC:2007
	Essential characteristics		Performance
	Reaction to fire	:	A1
			Minimum distances, in mm:
	Distance to combustible materials	:	rear = 170, sides = 10, floor = 0, ceiling = 600, front = 800
	Risk of burning fuel falling out	:	Pass
	Emission of combustion products	:	CO [0,07 %]
	Surface temperature	:	Pass
	Electrical safety	:	Pass
	Cleanability	:	Pass
	Maximum water operating pressure	:	bar
	Flue gas temperature at nominal heat output	:	T [191,4°C]
	Mechanical resistance	:	NPD
	Nominal heat output		8,0 kW
	Room heating output	:	8,0 kW
	Water heating output		kW
	Energy efficiency	:	η [80,2 %]
9.	The performance of the product identified in points 1 and 2 is in conformity with the declared		
5.	performance in point 8.		
	This declaration of performance is issued under the sole responsibility of the manufacturer		

Trodena n.P.N., November 16th 2017

identified in point 4.

