

Declaration of performance
according to Regulation (EU) 305/2011



Identification code: violino-45x60-gen-1
 Product: Violino 45x60
 Type / version: –
 Generation: 1
 Intended use: Inset appliance or open fire without hot water supply
 Manufacturer: Rüegg Cheminée Schweiz AG
 Studbachstrasse 7
 8340 Hinwil / Switzerland
 Authorised representative: –
 System of assessment and verification of constancy of performance: 3
 Notified laboratory: Rhein-Ruhr Feuerstätten Prüfstelle
 NB 1625
 Im Lipperfeld 34b
 46047 Oberhausen / Germany
 Test report: RRF-29 15 4144-1

Harmonized technical specification	EN 13229:2001 / A2:2004 / AC:2007		
Fire safety	Reaction to fire A1		
Minimum distance to combustible materials	Insulation thickness rear	15	cm
	Insulation thickness sides	15	cm
	Insulation thickness ceiling	–	cm
	Insulation thickness floor	4	cm
	Front	125	cm
Risk of burning fuel falling out	Pass		
Surface temperature	Pass		
Electrical safety	–		
Cleanability	Pass		
Mechanical resistance to carry a chimney / flue	NPD		
Emissions of combustion	CO (resp. 13 Vol-% O ₂)	1250	mg / m ³
	Dust (resp. 13 Vol-% O ₂)	11,0	mg / m ³
Maximum water operating pressure	–		bar
Flue gas temperature at nominal heat output	256		° C
Nominal heat output	8,4		kW
Room heating output	9,2		kW
Water heating output	–		kW
Energy efficiency	84,0		%

Hinwil, 28.01.2016

Name: Christoph Rutschmann
Director

Signature: