

Appliances properties: Wamsler Haus- und Küchentechnik GmbH - KF101-OST, GEA, GEH. SCHW. 8kW (bis 2011) - W20001018009

| Manufacturer Model Froduct code Nominal heat output [kW] Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas walues Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] | er Haus- und Küchentechnik GmbH OST, GEA, GEH. SCHW. 8kW (bis 2011) 1018009 |
|--|---|
| Manufacturer Model Froduct code Nominal heat output [kW] Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | er Haus- und Küchentechnik GmbH OST, GEA, GEH. SCHW. 8kW (bis 2011) 1018009 |
| Manufacturer Model Froduct code Nominal heat output [kW] Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | er Haus- und Küchentechnik GmbH OST, GEA, GEH. SCHW. 8kW (bis 2011) 1018009 |
| Model KF101 Product code W2000 Nominal heat output [kW] 8 Continuous burning appliance Type test standard DIN EN Year of testing 2006 Test laboratory RWE F Number of test laboratory 4.1 Number of test report FSPS- Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | OST, GEA, GEH. SCHW. 8kW (bis 2011) 1018009 13240 |
| Product code Nominal heat output [kW] Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas walues Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | 13240 |
| Nominal heat output [kW] Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas walues Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | 13240 |
| Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | |
| Year of testing 2006 Test laboratory RWE F Number of test laboratory 4.1 Number of test report FSPS- Flue gas wass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | |
| Test laboratory RWE F Number of test laboratory 4.1 Number of test report FSPS- Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | neinbraun AG |
| Number of test laboratory Number of test report FSPS- Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | neinbraun AG |
| Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | |
| Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | |
| Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] | Va 1361-EN |
| Flue gas mass flow [g/s] Necessary flue draught [Pa] | |
| Flue gas mass flow [g/s] Necessary flue draught [Pa] | Wood |
| Necessary flue draught [Pa] | 7 |
| | 350 |
| Further important characteristics of the appliance | 11 |
| Further important characteristics of the appliance | |
| Turner important characteristics of the appliance | |
| Suitability for installation to a shared flue ¹⁾ | |
| Connectivity to the central heating system | ✓ |

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation |
|---|------------------------|
| D - 1.BlmSchV | Stufe 2 |
| A - Austrian regulation referred to Art 15a B-VG | ✓ |
| CH - Swiss clean air act | ✓ |
| DK - Danish regulation for air pollution from wood burners | ✓ |
| F - Crédit d'impôt à la transition énergétique | √ 7 ☆ |

Evaluation of emission data and efficiency Lignite briquettes

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation |
|---|---------------------------|
| - 1.BImSchV | Stufe 1 Grandfathering |
| - Austrian regulation referred to Art 15a B-VG | ✓ |
| H - Swiss clean air act | • |



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information