

Appliances properties: Olsberg GmbH - Olsberg - Tolima Aqua Compact RLU (10 kW) - 23/559

Master data	
Date of entry	May 15, 2019
Manufacturer	Olsberg GmbH - Olsberg
Model	Tolima Aqua Compact RLU (10 kW)
Product code	23/559
Nominal heat output [kW]	10
Declared nominal space heating output [kW]	3
Nominal water heating output [kW]	7
Water operating pressure [bar]	2.5
Continuous burning appliance	_
Type test standard	DIN EN 13240
Year of testing	2009
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 40 09 1993

Flue gas values

	Wood
Flue gas mass flow [g/s]	9
Flue gas mass flow [g/s]	310
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	_
Connectivity to the central heating system	✓
General technical approval for room sealed operation	🖌 🖌
Number of approval for room sealed operation	Z-43.11-228

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	• • • • • • • • • • • • • • • • • • •
DK - Danish regulation for air pollution from wood burners	×
F - Crédit d'impôt à la transition énergétique	7★

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	
	A second way to the transmitter of while 200 the second second second suppli-

According to the transitional rule §26 the appliance can be used until 31.12.2024

Stufe 2	Compliant with the requirements of the 2nd stage of the 1.BImSchV (only for Germany)
Stufe 1	Compliant with the requirements of the 1st stage of the 1.BImSchV (only for Germany)
2015	Compliant with the requirements of the Austrian Agreement pursuant to Art. 15a B-VG from 2015 (applies only to Austria)
7☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 7* of the Flamme Verte Label
6 ☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 6* of the Flamme Verte Label
5☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 5* of the Flamme Verte Label
*	Compliant with the requirements of the 1 star stage in Italy.
क्रे क्रे	Compliant with the requirements of the 2 star stage in Italy.
* 京京	Compliant with the requirements of the 3 star stage in Italy.
***	Compliant with the requirements of the 4 star stage in Italy.
****	Compliant with the requirements of the 5 star stage in Italy.
	Fulfils the requirements
\checkmark	Complies with requirements of the transition ruling (1.BImSchV)
-	Requirements are not fulfilled
—	No information/unknown
!	No measuring values are available for this fuel, operation with this fuel is not permitted
No svi	nbol means that there are no requirements.

Here you will find further information