Appliances properties: Austroflamm GmbH - Ke 45x51 K mit Aufsatzregister

Master data	
Date of entry	Jan 3, 2012
Manufacturer	Austroflamm GmbH
Model	Ke 45x51 K mit Aufsatzregister
Nominal heat output [kW]	6
Continuous burning appliance	_
Type test standard	DIN EN 13229
Year of testing	2010
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 29 10 2473

Flue gas values

	Wood
Flue gas mass flow [g/s]	5.39
Flue gas mass flow [g/s]	276
Necessary flue draught [Pa]	12

Further important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾	✓	
Connectivity to the central heating system	-	
General technical approval for room sealed operation	✓	
Number of approval for room sealed operation	Z-43.12-273	

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	 Image: A set of the set of the
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	×
F - Crédit d'impôt à la transition énergétique	7☆
I - Italian Decree No. 186	म्हित्री

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	!