

Appliances properties: Supra S.A. - ASTRA-D - Marke Supra

Master data		
Date of entry	Feb 26, 2008	
Manufacturer	Supra S.A.	
Model	ASTRA-D	
Product code	Marke Supra	
lominal heat output [kW]	8	
ontinuous burning appliance	_	
ype test standard	DIN 18891	
ear of testing	2005	
est laboratory	RWE Rheinbraun AG	
lumber of test laboratory	4.1	
Number of test report	FSPS-WA-1329	

	Wood	
Flue gas mass flow [g/s]	10	
Flue gas mass flow [g/s]	350	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

_

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industriance and a Viberaby confirms compliance with the respective requirements.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024
A - Austrian regulation referred to Art 15a B-VG	_
CH - Swiss clean air act	_
DK - Danish regulation for air pollution from wood burners	!
F - Crédit d'impôt à la transition énergétique	_

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024
- Austrian regulation referred to Art 15a B-VG	_
CH - Swiss clean air act	· !



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information