

## Appliances properties: HOXTER a.s. - SF 70/40/38L

| Model  Nominal heat output [kW]  Continuous burning appliance  Type test standard  Year of testing  Test laboratory  Number of test laboratory | Oct 26, 2021 HOXTER a.s. SF 70/40/38L 33  DIN EN 13229 2016 Strojirensky Zkusebni Ustav s.p. |      |
|--|--|------|
| Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory                                      | SF 70/40/38L 33  DIN EN 13229 2016 Strojirensky Zkusebni Ustav s.p. 19                       |      |
| Nominal heat output [kW]  Continuous burning appliance  Type test standard  Year of testing  Test laboratory  Number of test laboratory        | DIN EN 13229 2016 Strojirensky Zkusebni Ustav s.p. 19  |      |
| Nominal heat output [kW]  Continuous burning appliance  Type test standard  Year of testing  Test laboratory  Number of test laboratory        | DIN EN 13229<br>2016<br>Strojirensky Zkusebni Ustav s.p.                                     |      |
| Type test standard<br>Year of testing<br>Test laboratory<br>Number of test laboratory  | DIN EN 13229<br>2016<br>Strojirensky Zkusebni Ustav s.p.<br>19                               |      |
| Year of testing<br>Fest laboratory<br>Number of test laboratory  | 2016<br>Strojirensky Zkusebni Ustav s.p.<br>19   |      |
| Test laboratory Number of test laboratory  | Strojirensky Zkusebni Ustav s.p. 19  |      |
| Number of test laboratory  | 19   |      |
| -  |  |      |
| Number of test report  |  |      |
|  | 30-12784-T-4   |      |
| Flue gas values  |  |      |
|  |  | Wood |
| Flue gas mass flow [g/s]   |  | 34.9 |
| Flue gas mass flow [g/s]   |  | 177  |
| Necessary flue draught [Pa]  |  | 10   |
|  |  |      |
| Further important characteristics of the appliance   |  |      |
| Suitability for installation to a shared flue <sup>1)</sup>  |  |      |

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

| Norm : Inset appliances (with closed firedoor)             | Evaluation  |
|--|-------------|
| D - 1.BlmSchV  | Stufe 2     |
| A - Austrian regulation referred to Art 15a B-VG           | 2015        |
| CH - Swiss clean air act                                   | <b>*</b>    |
| DK - Danish regulation for air pollution from wood burners | <b>*</b>    |
| F - Crédit d'impôt à la transition énergétique             | <b>√</b> 7★ |

## Evaluation of emission data and efficiency Lignite briquettes

| Norm : Inset appliances (with closed firedoor) | Evaluation |
|--|------------|
| D - 1.BlmSchV                                  | ļ.         |



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information