

Appliances properties: Spartherm Feuerungstechnik GmbH - Varia 1V H2O 9,0 kW - A1 (ab 01.2014)

Master data Date of entry Manufacturer Spartherm Feuerungstechnik GmbH Varia 1V H2O 9,0 kW - A1 (ab 01.2014) Nominal heat output [kW] 9 Continuous burning appliance Type test standard DIN EN 13229 Year of testing 2013 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory Number of test report RRF - 29 13 3358 Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]	
Manufacturer Model Varia 1V H2O 9,0 kW - A1 (ab 01.2014) Nominal heat output [kW] 9 Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Manufacturer Model Varia 1V H2O 9,0 kW - A1 (ab 01.2014) Nominal heat output [kW] 9 Continuous burning appliance Type test standard Year of testing 2013 Test laboratory Number of test laboratory Number of test report Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Further important characteristics of the appliance Further important characteristics of the appliance	
Model Nominal heat output [kW] Continuous burning appliance Type test standard DIN EN 13229 Year of testing 2013 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report RRF - 29 13 3358 Flue gas walues Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]	
Nominal heat output [kW] Continuous burning appliance Type test standard DIN EN 13229 Year of testing 2013 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report RRF - 29 13 3358 Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]	
Type test standard DIN EN 13229 Year of testing 2013 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report RRF - 29 13 3358 Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Year of testing Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory RRF - 29 13 3358 Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Year of testing Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory RRF - 29 13 3358 Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 RRF - 29 13 3358 Flue gas walues Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]	
Number of test report RRF - 29 13 3358 Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	
Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	Wood
Necessary flue draught [Pa] Further important characteristics of the appliance	7.9
Further important characteristics of the appliance	234
	12
Suitability for installation to a shared flue ¹⁾	~
Connectivity to the central heating system	•

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

EU-Inset appliance according to EN13229	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	*
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	*
CH - Swiss clean air act	*
DK - Danish regulation for air pollution from wood burners	*
F - Crédit d'impôt à la transition énergétique	7☆
I - Italian Decree No. 186	南南南

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	1



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information