

Appliances properties: Max Blank GmbH - Toulon/Toulon II (ab Seriennummer 4xxxxx)

Master data		
Date of entry	Dec 16, 2015	-
Manufacturer	Max Blank GmbH	
Model	Toulon/Toulon II (ab Seriennummer 4xxxxx)	
Nominal heat output [kW]	6.5	
Declared nominal space heating output [kW]	6.5	
Partial load [kW]	3.3	
Part load space heating output [kW]	3.3	ALCE ALCE
Continuous burning appliance	-	× 15 ×
Type test standard	DIN EN 13240	Internation of the
Year of testing	2011	
Test laboratory	Versuchs- und Forschungsanstalt der Hafner Österreichs	The second second
Number of test laboratory	8	
Number of test report	VFH-11-008-P	

Flue gas values

	Wood
Flue gas mass flow [g/s]	10.3
Flue gas mass flow [g/s]	268
Necessary flue draught [Pa]	12

 Further important characteristics of the appliance

 Suitability for installation to a shared flue¹⁾

 Connectivity to the central heating system

 General technical approval for room sealed operation

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood	
Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	×
F - Crédit d'impôt à la transition énergétique	7☆

Evaluation

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Interm	ittent burning): Roomheater with flat-layer firing
---------------------------	--

D - 1.BImSchV

Stufe 2	Compliant with the requirements of the 2nd stage of the 1.BImSchV (only for Germany)		
Stufe 1	Compliant with the requirements of the 1st stage of the 1.BImSchV (only for Germany)		
2015	Compliant with the requirements of the Austrian Agreement pursuant to Art. 15a B-VG from 2015 (applies only to Austria)		
7☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 7* of the Flamme Verte Label		
6 ☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 6* of the Flamme Verte Label		
5☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 5* of the Flamme Verte Label		
*	Compliant with the requirements of the 1 star stage in Italy.		
क्रे क्रे	Compliant with the requirements of the 2 star stage in Italy.		
* 京京	Compliant with the requirements of the 3 star stage in Italy.		
***	Compliant with the requirements of the 4 star stage in Italy.		
****	Compliant with the requirements of the 5 star stage in Italy.		
	Fulfils the requirements		
\checkmark	Complies with requirements of the transition ruling (1.BImSchV)		
—	Requirements are not fulfilled		
—	No information/unknown		
!	No measuring values are available for this fuel, operation with this fuel is not permitted		
No symbol means that there are no requirements.			

Here you will find further information