

Appliances properties: ORTNER GmbH - GO5 Tunnel Set

Master data	
Date of entry	Apr 30, 2025
Manufacturer	ORTNER GmbH
Model	GO5 Tunnel Set
Nominal heat output [kW]	2.7
Continuous burning appliance	_
Type test standard	In Anlehnung an EN 13229
Year of testing	2011
Test laboratory	Technische Universtität Wien
Number of test laboratory	7
Number of test report	PL-11001/1-P
Flue gas values	
	Wood
Flue gas mass flow [g/s]	22.8
Flue gas mass flow [g/s]	218

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Necessary flue draught [Pa]



18

Connectivity to the central heating system

1) For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm:	Evaluation
EU -	✓
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	✓
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	7

Evaluation of emission data and efficiency Lignite briquettes

Norm : Masonry heater	Evaluation
D - 1.BlmSchV	ļ.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown