

Appliances properties: Supra S.A. - Tertio 76 VL2D - Marke Supra

Master data		
Date of entry	Feb 26, 2008	
Manufacturer	Supra S.A.	
Model	Tertio 76 VL2D	
Product code	Marke Supra	
Nominal heat output [kW]	10	
Continuous burning appliance	_	
Type test standard	DIN 18895	
Year of testing	1995	

Year of testing 1995

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

Number of test laboratory 2

Number of test report RO-95 98 144, SGS-5970-44-12-06

Flue gas values

	Wood
Flue gas mass flow [g/s]	8
Flue gas mass flow [g/s]	420
Necessary flue draught [Pa]	14

Further important characteristics of the appliance

Suitability for installation to a shared flue¹⁾



Connectivity to the central heating system



General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV F - Crédit d'impôt à la transition énergétique Evaluation Evaluation Grandfathering

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)

Evaluation

D - 1.BlmSchV





No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information