

Appliances properties: Olsberg GmbH - Olsberg - HK 9 - 19/159

Master data

Date of entry Apr 6, 2011

Manufacturer Olsberg GmbH - Olsberg

Model HK 9

Product code 19/159

Nominal heat output [kW] 10

Continuous burning appliance

Type test standard DIN 18895

Year of testing 1988



Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BlmSchV	According to the transitional rule §26 the appliance can be used until 31.12.2020	
A - Austrian regulation referred to Art 15a B-VG	!	
CH - Swiss clean air act	!	
DK - Danish regulation for air pollution from wood burners	!	
F - Crédit d'impôt à la transition énergétique	ļ.	

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BImSchV		

According to the transitional rule §26 the appliance can be used until 31.12.2020



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information