

Appliances properties: skantherm GmbH & Co. KG - illumø IV

Date of entry Manufacturer Skantherm GmbH & Co. KG Model Illumø IV Nominal heat output [kW] Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas values Mar 6, 2012 Skantherm GmbH & Co. KG Illumø IV 9 Lillumø IV 10 Lillumø IV 10 Lillumø IV 10 Lillumø IV	
Manufacturer Model Model Nominal heat output [kW] Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Flue gas values Skantherm GmbH & Co. KG illumø IV 9 Continuous burning appliance DIN 18891 1994 Deutsche Kohle Marketing GmbH 22 91 92 13 Z	
Model illumø IV Nominal heat output [kW] 9 Continuous burning appliance Type test standard DIN 18891 Year of testing 1994 Test laboratory Deutsche Kohle Marketing GmbH Number of test laboratory 22 Number of test report 91 92 13 Z	
Nominal heat output [kW] Continuous burning appliance Type test standard Pear of testing Test laboratory Number of test laboratory Number of test report Deutsche Kohle Marketing GmbH 22 91 92 13 Z	
Type test standard Year of testing Test laboratory Number of test report DIN 18891 1994 Deutsche Kohle Marketing GmbH 22 Number of test report 91 92 13 Z	
Type test standard Year of testing Test laboratory Number of test laboratory Number of test report DIN 18891 1994 Deutsche Kohle Marketing GmbH 22 Number of test report 91 92 13 Z	
Year of testing Test laboratory Deutsche Kohle Marketing GmbH Number of test laboratory 22 Number of test report 91 92 13 Z Flue gas values	
Test laboratory Number of test laboratory Number of test report Deutsche Kohle Marketing GmbH 22 91 92 13 Z Flue gas values	
Number of test laboratory Number of test report 91 92 13 Z Flue gas values	
Number of test report 91 92 13 Z Flue gas values	
Flue gas values	
	Wood
Flue gas mass flow [g/s]	6
Flue gas mass flow [g/s]	417
Necessary flue draught [Pa]	10
Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	•

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm DIN EN 13240: Roomheater for wood logs	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	!
D - 1.BlmSchV	According to the transitional rule §26 the appliance can be used until 31.12.2020
A - Austrian regulation referred to Art 15a B-VG	
CH - Swiss clean air act	
DK - Danish regulation for air pollution from wood burners	
F - Crédit d'impôt à la transition énergétique	ļ.
I - Italian Decree No. 186	!

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	According to the transitional rule §26 the appliance can be used until 31.12.2020



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information