

Appliances properties: Uniproducts Industrial Limited - Tambora/UNI 1066-GTS

| Master data | | |
|---|--|------|
| Date of entry | ? | |
| Manufacturer | Uniproducts Industrial Limited | |
| Model | Tambora/UNI 1066-GTS | |
| Nominal heat output [kW] | 6 | |
| Continuous burning appliance | _ | |
| ype test standard | DIN EN 13240 | |
| fear of testing | 2008 | |
| Test laboratory | RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH | |
| Number of test laboratory | 2 | |
| Number of test report | RRF-40 08 1735 | |
| Flue gas values | | |
| | | Wood |
| Flue gas mass flow [g/s] | | 6 |
| Flue gas mass flow [g/s] | | 280 |
| Necessary flue draught [Pa] | | 12 |
| | | |
| Further important characteristics of the appliance | | |
| Suitability for installation to a shared flue ¹⁾ | | _ |
| Connectivity to the central heating system | | _ |
| General technical approval for room sealed operation | | _ |
| | | |

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV A - Austrian regulation referred to Art 15a B-VG CH - Swiss clean air act

Evaluation of emission data and efficiency Lignite briquettes

Norm: Inset appliances (with closed firedoor)

F - Crédit d'impôt à la transition énergétique

Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information