

## Appliances properties: LEDA Werk GmbH & Co. KG - DIAMANT H12 / DIAMANT H12 E

Date of entry

Mar 11, 2008

Manufacturer

LEDA Werk GmbH & Co. KG

Model

DIAMANT H12 / DIAMANT H12 E

Nominal heat output [kW]

11

Continuous burning appliance

Year of testing

2001

Test laboratory

RWE Rheinbraun AG

Number of test laboratory

4.1

RB BF1-Hn 999

Flue gas values

Number of test report

	Wood	
Flue gas mass flow [g/s]	10	
Flue gas mass flow [g/s]	150	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance

Suitability for installation to a shared flue<sup>1)</sup>

Connectivity to the central heating system

## General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

## Norm: Inset appliance with flat-layer firing D - 1.BImSchV A - Austrian regulation referred to Art 15a B-VG CH - Swiss clean air act F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Wood

## Norm: Inset appliance with flat-layer firing Evaluation D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2024 CH - Swiss clean air act



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information