

Appliances properties: Spartherm Feuerungstechnik GmbH - Varia FD (Bauart A; ab 2003)

Master data

Date of entry	Nov 26, 2011
Manufacturer	Spartherm Feuerungstechnik GmbH
Model	Varia FD (Bauart A; ab 2003)
Nominal heat output [kW]	11
Continuous burning appliance	
Type test standard	DIN 18895
Year of testing	2003
Test laboratory	DMT Feuerstätten Prüfstelle
Number of test laboratory	20
Number of test report	RO-95 02 489

Flue gas values

	Wood
Flue gas mass flow [g/s]	10
Flue gas mass flow [g/s]	355
Necessary flue draught [Pa]	10

Further important characteristics of the appliance

Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	
General technical approval for room sealed operation	

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a „1“ indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a „2“ indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)

Evaluation

D - 1.BImSchV


Grandfathering

A - Austrian regulation referred to Art 15a B-VG

—

CH - Swiss clean air act

—

F - Crédit d'impôt à la transition énergétique

—

Evaluation of emission data and efficiency Lignite briquettes





























Norm : Inset appliances (with closed firedoor)

Evaluation

D - 1.BImSchV

!
According to the transitional rule §26 the appliance can be used until
31.12.2024

Emission evaluation legend

-    Compliant with the requirements of the 2nd stage of the 1.BImSchV (only for Germany)
-   Compliant with the requirements of the 1st stage of the 1.BImSchV (only for Germany)
-   2015 Compliant with the requirements of the Austrian Agreement pursuant to Art. 15a B-VG from 2015 (applies only to Austria)
-   7★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 7* of the Flamme Verte Label
-   6★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 6* of the Flamme Verte Label
-   5★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 5* of the Flamme Verte Label
-   ★ Compliant with the requirements of the 1 star stage in Italy.
-   ★★ Compliant with the requirements of the 2 star stage in Italy.
-   ★★★ Compliant with the requirements of the 3 star stage in Italy.
-   ★★★★ Compliant with the requirements of the 4 star stage in Italy.
-   ★★★★★ Compliant with the requirements of the 5 star stage in Italy.
-  Fulfils the requirements
-  Complies with requirements of the transition ruling (1.BImSchV)
-  Requirements are not fulfilled
-  No information/unknown
-  ! No measuring values are available for this fuel, operation with this fuel is not permitted

No symbol means that there are no requirements.

Here you will find further information