

Appliances properties: Austroflamm GmbH - Amigo

Master data

Date of entry Jan 9, 2012

Manufacturer Austroflamm GmbH

Model Amigo

Nominal heat output [kW] 6

Declared nominal space heating output [kW] 6

Continuous burning appliance

Thermal output 21,600

Type test standard DIN 18891

Year of testing 1995

Test laboratory RWE Rheinbraun AG

Number of test laboratory 4.1

Number of test report RB BF1-Hn 63/95

Flue gas values

	Wood
Flue gas mass flow [g/s]	8
Flue gas mass flow [g/s]	285
Necessary flue draught [Pa]	12

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing D - 1.BlmSchV According to the transitional rule §26 the appliance can be used until 31.12.2024

Evaluation of emission data and efficiency Lignite briquettes

Evaluation of emission data and efficiency Wood

F - Crédit d'impôt à la transition énergétique

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information