

Appliances properties: HWAM A/S - HWAM 3640c IHS mit Steinverkleidung

Master data		
Pote of outer	Day 40, 0045	
Date of entry	Dec 16, 2015	
Manufacturer	HWAM A/S	
Model	HWAM 3640c IHS mit Steinverkleidung	
Nominal heat output [kW]	6.4	
Continuous burning appliance	_	
Type test standard	DIN EN 13240	
Year of testing	2012	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Number of test laboratory	2	
Number of test report	RRF - 40 12 3050	
Flue gas values		
		Wood
Flue gas mass flow [g/s]		5.04
Flue gas mass flow [g/s]		325
Necessary flue draught [Pa]		12
Further important characteristics of the appliance		
runner important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾		✓

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation	
D - 1.BlmSchV	Stufe 2	
A - Austrian regulation referred to Art 15a B-VG	2015	
CH - Swiss clean air act	✓	
DK - Danish regulation for air pollution from wood burners	✓	
F - Crédit d'impôt à la transition énergétique	7☆	

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information