

Appliances properties: Supra S.A. - Obernai D - Marke Supra

| Date of entry | Feb 26, 2008 |
|------------------------------|-------------------|
| lanufacturer | Supra S.A. |
| odel | Obernai D |
| Product code | Marke Supra |
| lominal heat output [kW] | 7 |
| Continuous burning appliance | _ |
| ype test standard | DIN 18891 |
| ear of testing | 1995 |
| est laboratory | RWE Rheinbraun AG |
| Number of test laboratory | 4.1 |
| Number of test report | RB BF1-Hn 07/95 |

| Flue | aas | values | |
|------|-----|--------|--|
| | | | |

| | Wood |
|-----------------------------|------|
| Flue gas mass flow [g/s] | 5 |
| Flue gas mass flow [g/s] | 299 |
| Necessary flue draught [Pa] | 10 |

Further important characteristics of the appliance

Suitability for installation to a shared flue $^{1)}$



Connectivity to the central heating system

_

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation |
|---|---|
| D - 1.BlmSchV | According to the transitional rule §26 the appliance can be used until 31.12.2024 |
| A - Austrian regulation referred to Art 15a B-VG | _ |
| CH - Swiss clean air act | _ |
| DK - Danish regulation for air pollution from wood burners | ! |
| F - Crédit d'impôt à la transition énergétique | _ |

Evaluation of emission data and efficiency Lignite briquettes

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation |
|---|---|
| D - 1.BImSchV | According to the transitional rule §26 the appliance can be used until 31.12.2024 |
| - Austrian regulation referred to Art 15a B-VG | _ |
| CH - Swiss clean air act | · ! |



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information