

## Appliances properties: Spartherm Feuerungstechnik GmbH - Speedy MR S (Bauart A1; ab 07.2012)

| Master data   |  |             |
|---|--|-------------|
| Date of entry   | Feb 18, 2015                               |             |
| Manufacturer  | Spartherm Feuerungstechnik GmbH            |             |
| Model   |  |             |
| Nominal heat output [kW]                                    | 7  |             |
| Continuous burning appliance                                | _  |             |
| Type test standard  | DIN EN 13229                               |             |
| Year of testing   | 2011                                       |             |
| Test laboratory   | RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH |             |
| Number of test laboratory                                   | 2  |             |
| Number of test report                                       | RRF - 29 10 2547                           |             |
| Flue gas values   |  |             |
| Flue gas mass flow [g/s]                                    |  | Wood<br>6.2 |
| Flue gas mass flow [g/s]                                    |  | 341         |
| Necessary flue draught [Pa]                                 |  | 12          |
| Nescessary has draught [1 a]                                |  | 12          |
| Further important characteristics of the appliance          |  |             |
| Suitability for installation to a shared flue <sup>1)</sup> |  | <b>✓</b>    |
| Connectivity to the central heating system                  |  | -           |

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

| EU-Inset appliance according to EN13229                    | Evaluation |
|--|------------|
| EU - Regulation (EU) 2015/1185 (Ecodesign)                 | <b>*</b>   |
| D - 1.BlmSchV  | Stufe 2    |
| A - Austrian regulation referred to Art 15a B-VG           | ✓          |
| CH - Swiss clean air act                                   | ✓          |
| DK - Danish regulation for air pollution from wood burners | ✓          |
| F - Crédit d'impôt à la transition énergétique             | 7☆         |
| I - Italian Decree No. 186                                 | <b>华州</b>  |

## Evaluation of emission data and efficiency Lignite briquettes

| Norm : Inset appliances (with closed firedoor) | Evaluation |
|--|------------|
| D - 1.BlmSchV                                  | 1          |



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information